



## Premises Identification

### SECTION 505 - PREMISES IDENTIFICATION

**Section 505.1 Address identification.** Is hereby **Deleted** (in its entirety) **and REPLACED** with:

**Section 505.1 Address identification.** New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property. Where required by the fire code official, address numbers shall be provide in additional approved locations to facilitate emergency response.

#### **Commercial**

Building < 50 feet from the curb require 12" numbers displayed on the building.  
Buildings > 50 feet from the curb require 15" numbers displayed on the building.  
Tenant space numbers shall be 3"  
Address range may be displayed in 12" numbers on the building,

#### **Apartments**

Entrance numbers shall be 12"  
Building numbers shall be 15"  
Apartment numbers ranges displayed below building numbers shall be 8";  
Apartment numbers ranges displayed on signage near the building shall be 2";  
Apartment numbers shall be 3" on outside entrances and 1" for interior (hallway) entrances;  
Number ranges are required on buildings or signage.

#### **Residential**

< 50 feet from curb requires 3" numbers displayed on the building.  
>50 feet from the curb requires 3" numbers displayed a minimum of 36" above ground at the primary access point.

#### **RV and Mobile Home Parks**

Entrance numbers shall be minimum 12"; Building numbers 6"; Space numbers 3"

#### **Miscellaneous Information**

The complete address shall be displayed on all corner buildings.  
Addresses shall be displayed and visible from both directions of approaching vehicles.  
Numbers and letters shall be made of durable material. (Paint is not acceptable)  
Numbers and letters shall be of colors contrasting with the background  
Numbers and letters shall have a min. proportion ratio of 6:1 (height to width).  
Numbers shall not be spelled.  
Address numbers shall be maintained.